according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : APESIN HANDACTIVE F UFI : DNX8-50VA-D00D-ADXF

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Biocidal product

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH

Rheinallee 96 55120 Mainz

Telephone : +49613196403 Telefax : +4961319642414

E-mail address : Produktsicherheit@werner-mertz.com

Responsible/issuing person

Contact person : Product development / product safety

1.4 Emergency telephone number

112

Centru za kontrolu otrovanja u Zagrebu na tel. (01) 2348 342

+49(0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

Supplemental Hazard : EUH

Statements

EUH066 Repeated exposure may cause skin dryness or

cracking.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed. P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/

doctor.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of container into the collection of

recyclables only when it is completely empty.

Hazardous components which must be listed on the label:

propan-2-ol

propan-1-ol

Safety data sheet available on request.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 40 - < 50
propan-1-ol	71-23-8 200-746-9 603-003-00-0 01-2119486761-29	Flam. Liq. 2; H225 Eye Dam. 1; H318 STOT SE 3; H336	>= 25 - < 40

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Call a POISON CENTER or doctor/ physician.

Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Take off contaminated clothing and shoes immediately.

Wash clothing before reuse.

Call a POISON CENTER or doctor/ physician.

Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue

damage and blindness. Protect unharmed eye.

If easy to do, remove contact lens, if worn.

Rinse thoroughly with plenty of water for at least 15 minutes and

consult a physician.

Continue rinsing eyes during transport to hospital.

Small amounts splashed into eyes can cause irreversible tissue

damage and blindness. Protect unharmed eye.

Continue rinsing eyes during transport to hospital.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects

Risks : No information available.

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons

Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Water spray jet Dry powder

Alcohol-resistant foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for :

firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This must

not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national



WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

regulations (see section 13).

Use mechanical handling equipment.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., For disposal considerations see section 13., Refer to section 15 for specific national regulation. For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application

area.

Take precautionary measures against static discharges.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.

Advice on protection against fire

and explosion

Use explosion-proof equipment. Avoid formation of aerosol. Keep away from sources of ignition - No smoking. Take measures to

prevent the build up of electrostatic charge.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas

and containers

Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept
upright to prevent leakage. Electrical installations / working materials
must comply with the technological safety standards. Store at room

temperature in the original container.

Store in original container. Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Store

at room temperature in the original container.

Further information on storage

stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Biocidal product

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection : not required under normal use

If splashes are likely to occur, wear:

Tightly fitting safety goggles

If splashes are likely to occur, wear:

Tightly fitting safety goggles

Hand protection

Material : not required under normal use

Material : For prolonged or repeated contact use protective gloves.

It is suggested the usage of chemical resistant gloves made of butyl

rubber or nitrile rubber category III according to EN 374.

As alternative, a different type of gloves might be used if,

accordingly to the recommendations of the producer, guarantee the

same level of protection.

Remarks : Take note of the information given by the producer concerning

permeability and break through times, and of special workplace

conditions (mechanical strain, duration of contact).

Skin and body protection : not required under normal use

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour colourless Odour alcohol-like

Melting point/freezing point : No data available Boiling point/boiling range : No data available Flammability (solid, gas) : No data available Flammability (liquids) : No data available No data available Lower explosion limit Upper explosion limit No data available

Flash point 23 °C

Ignition temperature : No data available Decomposition temperature : No data available

pΗ ca. 5,4, 1 %

at 20 °C

Viscosity, dynamic No data available No data available Viscosity, kinematic

Water solubility soluble

Solubility in other solvents : No data available Partition coefficient: n-No data available

octanol/water

Vapour pressure : No data available

: ca. 0,852 g/cm3 at 20 °C Density

Relative density : No data available Relative vapour density No data available Particle characteristics : No data available

9.2 Other information

none

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if used as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.

Our company does not place any orders for animal testing for the finished product or the ingredients. However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Acute toxicity : Not Rated

Components:

propan-2-ol

67-63-0:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

Method: OECD Test Guideline 401

LD50 Oral (Rat): 4.570 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 47,5 mg/l

Exposure time: 8 h

Method: OECD Test Guideline 403

LC50 (Rat): 72,6 mg/l Exposure time: 4 h

LC50 (Mouse): 27,2 mg/l

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Exposure time: 4 h

LC50 (Rat): 25 mg/l Exposure time: 6 h

Method: OECD Test Guideline 403

LC50 (Rat): 30 mg/l Exposure time: 4 h

LC50 (Rat): 10000 ppm Exposure time: 6 h

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

Method: OECD Test Guideline 402

LD50 Dermal (Rabbit): 12.870 mg/kg Method: OECD Test Guideline 402 LD50 Dermal (Rabbit): 13.900 mg/kg Method: OECD Test Guideline 402

LD50 Dermal (Rabbit): 13.400 mg/kg

propan-1-ol

71-23-8:

Acute oral toxicity : LD50 Oral (Rat): 1.870 mg/kg

LD50 (Rat): ca. 8.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 33,8 mg/l

Exposure time: 4 h

LC50 (Rat): 39,1 mg/l Exposure time: 1 h

Acute dermal toxicity : LD50 (Rabbit): 4.000 - 10.000 mg/kg

LD50 (Rabbit): 4.032 mg/kg

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

propan-2-ol

67-63-0:

Species : Rabbit

Result : No skin irritation

propan-1-ol

71-23-8:

Result : Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Components:

propan-2-ol

67-63-0:

Species : Rabbit Result : irritating

Respiratory or skin sensitisation

Product:

Remarks : No data available

Components:

propan-2-ol

67-63-0:

Test Type : Buehler Test Species : Guinea pig

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Germ cell mutagenicity : Not Rated

Components:

propan-2-ol

67-63-0:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

propan-1-ol

71-23-8:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT - single exposure : The substance or mixture is not classified as specific target organ

toxicant, single exposure.

STOT - repeated exposure : The substance or mixture is not classified as specific target organ

toxicant, repeated exposure.

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Aspiration toxicity : Not Rated

11.2 Information on other hazards

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

propan-2-ol 67-63-0:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.400 mg/l

Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l

Exposure time: 96 h

LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l

Exposure time: 48 h Test Type: static test

GLP: no

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 13.299 mg/l

Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): 9.714 mg/l

Exposure time: 24 h

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

GLP: no

(Daphnia (water flea)): > 10.000 mg/l Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 30 mg/l

Exposure time: 21 d

EC50 (Daphnia magna (Water flea)): 10.000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic plants : IC50 (Desmodesmus subspicatus (green algae)): > 1.000 mg/l

Exposure time: 72 h
Test Type: Growth inhibition

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 100 mg/l



WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Exposure time: 72 h Test Type: static test

GLP: no

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l

Exposure time: 72 h

EC50 (Scenedesmus subspicatus): > 100 mg/l

Exposure time: 72 h Test Type: static test

Toxicity to microorganisms : EC50 (Aliivibrio fischeri): 17.700 mg/l

Exposure time: 5 min

EC10 (Pseudomonas putida): 5.175 mg/l

Exposure time: 18 h Method: DIN 38412

propan-1-ol

71-23-8:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.555 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 3.644 mg/l

Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2.

EC50 (Daphnia magna (Water flea)): 3.640 - 8.150 mg/l

Exposure time: 48 h

Toxicity to microorganisms : EC50 (Photobacterium phosphoreum): 17,7 g/l

Exposure time: 5 min

EC0 (Pseudomonas putida): 2.700 mg/l

Exposure time: 16 h

IC50 (Bacteria): > 10.000 mg/l

Exposure time: 16 h

EC0 (see user defined free text): 3.100 mg/l

12.2 Persistence and degradability

Components:

propan-2-ol 67-63-0:

Biodegradability : Result: rapidly biodegradable

Biodegradation: 95 % Exposure time: 21 d Method: OECD 301 E

Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 53 %

Exposure time: 5 d

Result: rapidly biodegradable Biodegradation: > 70 %

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Exposure time: 10 d

GLP: no

Biodegradation: 99,9 %

Method: see user defined free text

Chemical Oxygen Demand

(COD)

2,32 g/kg

ThOD : 2,40 g/g

propan-1-ol

71-23-8:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 75 % Exposure time: 20 d Method: Closed Bottle test

Result: rapidly biodegradable

Biodegradation: 83 % Exposure time: 5 d Method: OECD 301 D

Result: rapidly biodegradable Biodegradation: 83 - 92 % Exposure time: 28 d Method: OECD 301 F

Chemical Oxygen Demand

(COD)

2,23 g/g

ThOD : 2,4 g/g

12.3 Bioaccumulative potential

Components:

propan-2-ol 67-63-0:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-

octanol/water

log Pow: 0,05

propan-1-ol

71-23-8:

Bioaccumulation : Bioconcentration factor (BCF): 3

Partition coefficient: n-

octanol/water

log Pow: 0,26

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

12.4 Mobility in soil

Components:

propan-2-ol 67-63-0:

Distribution among : Koc: 25

environmental compartments Remarks: Highly mobile in soils

propan-1-ol 71-23-8:

Distribution among : Koc: 33

environmental compartments Remarks: Highly mobile in soils

12.5 Results of PBT and vPvB assessment

Components:

propan-2-ol 67-63-0:

Assessment : This substance is not considered to be very persistent and very

bioaccumulating (vPvB).. This substance is not considered to be

persistent, bioaccumulating and toxic (PBT).

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemical or

used container.

In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : 1987 IMDG : 1987 IATA : 1987

14.2 UN proper shipping name

ADR : ALCOHOLS, N.O.S.



WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

(isopropanol)

IMDG : ALCOHOLS, N.O.S.

(isopropanol)

IATA : ALCOHOLS, N.O.S.

14.3 Transport hazard class(es)

ADR : 3 IMDG : 3 IATA : 3

14.4 Packing group

ADR

Classification Code : F1
Packaging group : III
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packaging group : III
Labels : 3
EmS Number : F-E, S-D

IATA

(Cargo) : ALCOHOLS, N.O.S., Alcohols, n.o.s.

Packaging group : III Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no IATA

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous

chemicals

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

: Not applicable

15 / 17

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident

hazards involving dangerous substances.

Quantity 1

Quantity 2

P5c

FLAMMABLE LIQUIDS

5.000 000067

50.000 000067

TA Luft List (Germany)

Total dust: Not applicable

Inorganic substances in powdered form: Not applicable

Inorganic substances in vapour or gaseous form: Not applicable

Organic Substances: Not applicableCarcinogenic substances: Not applicable

: Mutagenic: Not applicable

: Toxic to reproduction: Not applicable

Volatile organic compounds

(VOC) content

Directive 2010/75/EU of 24 November 2010 on industrial emissions

(integrated pollution prevention and control)

Update: Percent volatile: 75 %

804,34 q/l

VOC content excluding water

Volatile organic compounds

(VOC) content

Directive 2010/75/EU of 24 November 2010 on industrial emissions

(integrated pollution prevention and control)

Update: Percent volatile: 75 %

639 g/l

VOC content valid only for coating materials used on wood surfaces

according to Detergents Regulation EC 648/2004 : disinfectants

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Dam. : Serious eye damage Eye Irrit. : Eye irritation Flam. Liq. : Flammable liquids

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration

according to Regulation (EC) No. 1907/2006



APESIN HANDACTIVE F

WM 1116199 Order number: 0716199

Version 3.16 Revision Date 21.03.2024 Print Date 24.10.2024

associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

500000004889